



HDS 13/35 De Tr1


The HDS 13/35 trailer can be used self-sufficiently and reaches pressures of 350 bar. It is the perfect solution for hot water high-pressure cleaning in the municipal sector, at construction sites and in industry.

















1 Maximum efficiency

- Highly efficient, tried-and-tested burner technology.
- Heat recovery through use of waste heat from the engine.

2 Easy operation

- The machine is easy to operate using a central selector switch.
- Two optional hose reels in operating area allow easy set-up and dismantling.

3 Self-sufficient application

- Large 500-litre water tank for cleaning applications of up to 30 minutes at full water power.
- 100-litre diesel tank: ideal for long periods of use.

4 High flexibility

- Thanks to its configurability, each trailer can be custom-made according to customer requests.
- Skid and Cab versions make different uses possible: mobile or stationary.

TECHNICAL DATA AND EQUIPMENT





HDS 13/35 De Tr1

- Automatic speed reduction
- Speed regulation
- Stationary and mobile versions available

Technical data		
Order no.		1.524-521.2
Motor manufacturer		Yanmar
Motor type		19 kW Yanmar Motor
Fuel		Diesel
Engine rating	kW / hp	19 / 26
Flow rate	l/h	650 - 1300
Pressure	bar / MPa	100 - 350 / 10 - 35
Diesel consumption, full load	kg/h	12.4
Number of simultaneous users		1
Portability		Trailer
Weight	kg	950
Dimensions (L × W × H)	mm	3646 × 1747 × 1735

Equipment		
Spray gun		Industry
High-pressure hose	m	30
Spray lance	mm	700
Power nozzle		I
Servo control		-
Pressure adjustment over speed re	egu-	•

■ Included in the scope of supply.

HDS 13/35 DE TR1 1.524-521.2





		Order no.			Price	Description
Coupling						
Coupler -2 × M22 × 1,5	1	4.403-002.0				For overriding the dismantled heating coil for cleaningalter- native:4.111-029.0 adapter 1 - hose old / hose new

[☐] Available accessories.

HDS 13/35 DE TR1 1.524-521.2

























		Ordon	Longth				Duiso	Passwintian	
		Order no.	Length			<u> </u>	Price	Description	\perp
High-pressure hoses	1 4	L c 201 05C 0	1			1 1		CEO how M 22 v 4 E	1
Pressure hose	1	6.391-856.0						650 bar, M 22 x 1.5.	1
	2	6.391-848.0	-					650 bar, M 22 x 1.5	
	3	6.391-857.0	-					650 bar, M 22 x 1.5.	
	4	6.391-846.0						650 bar, M 22 x 1.5	
	5	6.391-847.0	-					650 bar, M 22 x 1.5.	
	6	6.391-019.0						Durable, abrasion-resistant and flexible multi-layer steel-rinforced hose with connection size M 22 × 1.5. Suitable for up to 620 bar working pressure.	
Couplings and connectors									
Coupling	7	4.403-004.0						For joining and extending HD hoses. Connection 2 × M 22 : 1.5. Material: Stainless steel.	۱ ا
Trigger guns								,	٠,
Kärcher industry gun	8	4.775-824.0						650 bar – industrial spray gun with optimised flow. Robust ness and durability for professional use. Food-safe and saltwater-resistant materials. Connector for HP hoses M 22 x 1.5.	Г
Shoulder support	9	2.639-251.0						Sturdy shoulder support that must be used from a recoil force of more than 150 N. Fits all Karcher industrial lances	j. [
Spray lances									
Spray lance	10	4.760-679.0						With nozzle holder.	[
	11	4.760-653.0							[
Jet pipe complete 1550 mm 65 MPa	12	4.760-675.3]
Spray lance	13	4.760-677.0							[
Power nozzles			1	1				1	
Flat jet nozzle	14	5.765-190.0						15° flat jet nozzle 15051 for high-pressure cleaner HD 13/35. Suitable for working pressures of up to 350 bar and 1,300 l/h (HDS trailer).	d [
Single-jet rotary nozzles									
Rotary jet	15	4.767-173.0						350 bar, 1.35 mm, 1,300 l/h, M 20 × 1, brass.	[
Power rotary jet F7	16	6.415-914.0						350 bar, 1.35 mm, 1,300 l/h, M 20 × 1, stainless steel.	[
Power rotary jet repair kit F7	17	6.025-436.0						Repair kit for power rotary jet, order no. 6.415-914.0. Suit ble for 350 bar working pressure and 1,300 l/h water flow rate. Includes rotor, seat and 0-ring (28 × 2).	
Tool for changing rotor seat	18	6.025-233.0						For F3, F4, F1, F25.	[
Multi-jet rotary nozzles									
Nozzle body	19	9.917-677.0						Rotary transmission lead-through with infinitely variable speed control. Includes protective pipe.	[
Nozzle carrier head TD09	20	9.899-828.0						6-jet nozzle carrier head for F21 nozzle. Suitable for work ing pressures of up to 3,000 bar. 35° spray angle, includes guard and flow conditioner.	- 1
Screw nozzles F21					,				
Dummy nozzle F21	21	6.025-237.0						F21 screw-on dummy nozzle. Suitable for working pressur of up to 3,000 bar.	es [
Round jet nozzle F21, Saphir	22	9.886-216.0						Screw-on F21 sapphire round jet nozzle with a diameter of 0.90 mm. Suitable for working pressures of up to 3,000 ba	
Pipe cleaning Foot valve for pipe cleaning	23	6.470-223.0						Foot valve for convenient and safe use of accessories for effective pipe cleaning.	

HDS 13/35 DE TR1 1.524-521.2















		Order no.	Length		Price	Description	
Pipe cleaning nozzle standard 050 50MPa	24	4.765-012.0				Standard pipe cleaning nozzle for pipe cleaning hoses with G1/4" threaded connection. Nozzle configuration: 3x backward.	
Pipe cleaning nozzle Four 050 50MPa	25	4.765-016.0				For pipe cleaning hoses with G1/4" threaded connection: Quattro pipe cleaning nozzle. Nozzle configuration: 3x backward and 1x forward.	
Pipe cleaning nozzle, Rotor	26	5.763-092.0				For pipe cleaning hoses with G1/4" threaded connection: Rotor pipe cleaning nozzle. Nozzle configuration: 3x backward.	
Pipe cleaning hose	27	6.392-401.0				Flexible pressure hose (DN 8) for thorough pipe cleaning. 10 m long. Threaded connection for G1/4" nozzle.	
	28	6.392-402.0				Flexible pressure hose (DN 8) for thorough pipe cleaning. With threaded connection for G1/4" nozzle and 20 m long.	
	29	6.392-403.0				For through pipe cleaning: flexible, 30 m long pressure hose with threaded connection for G1/4" nozzle.	
Surface cleaner							
Surface Cleaner FRI 50 Me	30	2.643-577.0				Surface cleaner for efficient cleaning of surfaces up to 500 bar and hot water cleaning up to 100°C. 4 convenient steering rollers. Specific nozzle kits must be ordered separately.	
Nozzle package 025 FRI 50 Me	31	6.415-045.0				Nozzle kit specifically for FRI 50 Me Surface Cleaner. Nozzle size: 025.	
Abrasive blaster							
Required adapter for abrasive blasters	32	5.401-325.0				M 20 x 1 IG to 9/16" UNF AG.	
Abrasive blaster, incl. 3 x 0.7 nozzle	33	9.872-435.0				Abrasive spray head with nozzle size 3 × 0.7 mm for wet sand blasting. Only includes spray head. Without hose and lance.	
Replacement nozzle for abrasive blaster	34	6.025-346.0				Replacement nozzle for abrasive spray head made from boron carbide. Colour blue.	
F98 nozzle kit, D 0.70 mm	35	9.886-551.0				For wet sand blasting: three-nozzle kit for abrasive spray head. Nozzle size 0.7 mm.	
F98 nozzle for abrasive blaster	36	6.025-255.0				Nozzle (nozzle size 0.7 mm) for abrasive spray head for wet sand blasting.	

[☐] Available accessories.